


Zulassungen | Certificates



EUROTEC Antriebszubehör GmbH

Bildstock 37
DE-88085 Langenargen
Germany

Tel. +49 7543 93463-0
Fax +49 7543 93463-10
e-Mail sales@eurotec.global
web www.eurotec.global



Technik trifft Design ...
Designed **technology** ...



Kurz gesagt:

- > Unsere kleinste Endschalterbox
- > Direktaufbau ohne Montagebrücke
- > Besonders geeignet für kleine Pneumatik Antriebe
- > Passend für Anwendung mit wenig Platz
- > Super schnelle und einfache Montage
- > 1x Anschlussgewinde M20x1,5 standardmäßig

Quick facts

- > Our smallest limit switch box
- > Direct mounting without mounting bracket
- > Perfect fit for small pneumatic actuators
- > Suitable for applications with limited space
- > Fast and effortless assembly
- > 1x connection thread M20x1,5 as standard

i-box[®]

Mounted in no time - the i-box advantage!

OPTISCHE ANZEIGEN | VISUAL INDICATORS



Standard
OPEN/CLOSED

Standard
OPEN/CLOSED



2D (L/T-Bohrung)

2D (L/T-bore)



180° Skala

180° scale



LED-Anzeige

LED indicator

GEHÄUSE | HOUSING



versch. Farben

different colours



Polyamid

Polyamid



Vestamid

Vestamid

EINFACHE MONTAGE | SIMPLE ASSEMBLY



Adaption

adaption



20 mm / 30 mm

20 mm / 30 mm



formschlüssig

form-locked



kraftschlüssig

actuated by screw

IHR LOGO YOUR LOGO



ab 1 Stk.
(nicht-Ex)
off 1 pc.
(non-Ex)

MEMBRAN MEMBRANE



Außenaufstellung
outdoor use

SENSOREN | SWITCHES



mechanisch

mechanical



induktiv

inductive



AS-i Anbindung

AS-i connection

ANSCHLÜSSE | CONNECTIONS



1 x M20x1,5 Kabel-
verschraubung

1 x M20x1,5 cable
gland



M12

M12



NPT 1/2

NPT 1/2

MAGNETVENTIL | SOLENOID VALVE



1 Spule,
monostabil

1 coil,
monostable



2 Spulen, bistabil

2 coils, bistable



MA12, max.
2 Spulen

MA12, max.
2 coils